

COLD FOOD HOLDERS {BAR COMBO'S} STAINLESS STEEL PUMPS

SB-3, SB-3 DI SB-4, SB-4 DI

Models SB-2, SB-2 DI

Date: Project: Quantity: Item Number:









THIN THICK PARTICULATE

See category tab for details.

Bid Description

Insulated serving bars are constructed of a stainless steel exterior with a one-piece seamless plastic interior. Serving Bars can be cooled with ice, (1) Eutectic Ice Pack (94141) per jar or our deep fountain HOLDCOLD™ jars (not included).

Pump combination models come complete with multiples of: deep polypropylene fountain jars (82557) and CP-F (83330) pumps. Choose from countertop or drop-in models.

Stainless steel CP-F condiment pumps feature a rugged cast valve body and welded construction. Maximum stroke yields $1\frac{1}{4}$ ounce (37 mL) with gauging collars supplied to reduce yield in $\frac{1}{8}$ ounce (3.7 mL) increments.

Standard Features

upon request

Stainless steel exterior, seamless plastic interior, and insulation Maximum stroke yields 1 ¼ oz (37 mL), now adjustable in ⅓ oz (3.7 mL) increments — allows for Portion Optimization ™ Stainless steel hinged lid attaches to lid in a snap Colored, engraved knobs to identify contents are available

Insulated Bar Combo's with Pumps

<u>Includes</u>	Countertop	<u>Drop-In</u>
(2) jars	SB-2 79890	SB-2 DI 79950
(3) jars	SB-3 83790	SB-3 DI 83860
(4) jars	SB-4 83700	SB-4 DI 83720

Insulated Bar - Base Only

To put together your own combination, choose a base unit from below and components from the Bar & Rail Accessory sheet.

<u>Accepts</u>	<u>Countertop</u>	<u>Drop-In</u>
(2) jars	SB-2 80160	SB-2 DI 80150
(3) jars	SB-3 83760	SB-3 DI 83830
(4) jars	SB-4 83600	SB-4 DI 83620

Warranty


Server Products equipment is backed by a two-year limited warranty against defects in materials and workmanship. For our complete warranty statement, please see our web site.

SB-4, SB-4 DI




COLD FOOD HOLDERS {BAR COMBO'S} STAINLESS STEEL PUMPS


Serving Bar—Counter-top



Serving Bar-Drop-In



Serving Bar-Counter-top & Drop-in



Specifications

Specificali	0 113			
Construction	Stainless steel exterior, seamless plastic interior, and insulation.			
Jar Capacity	Shallow 2 qt	3 ½ qt	HOLDCOLD™ 2 1/4 qt	
	1.9 L	3.3 L	2.1 L	
Counter-Top	(2) Jar	(3) Jar	(4) Jar	
A-Height in	193/8	19 ³ / ₈	19 ³ / ₈	
cm_	49.2	49.2	49.2	
B-Width in	10 1/8	15 1/2	20 1/8	
cm	27.6	39.4	51.1	
C-Depth in	8 13/16	8 13/16	8 13/16	
cm	22.4	22.4	22.4	
D-Spout in	31/4	31/4	31/4	
{Depth} cm	8.3	8.3	8.3	
Drop-In	(2) Jar	(3) Jar	(4) Jar	
E-Height in	67/16	6 ⁷ /16	67/16	
cm	16.4	16.4	16.4	
B-Width in	10 1/8	15 1/2	20 1/8	
cm	27.6	39.4	51.1	
C-Depth in	8 13/16	8 13/16	8 13/16	
cm	22.4	22.4	22.4	
F_Spout in	$2^{13}/_{16}$	213/16	213/16	
{Depth} cm	7.1	7.1	7.1	
Cutout Size				
SB-2 DI	11 x 8 7/8" (27.9 x 22.5 cm)			
SB-3 DI	· · · · · · · · · · · · · · · · · · ·			
SB-4 DI 20 1/4 x 8 7/8" (51.4 x 22.5 cm)				

FOB Richfield, Wisconsin 53076

CAD Library

Individual CAD images can be downloaded from product pages on our web site. We are also a member of The KCL CADalog with more than 100 other manufacturers. Our complete collection of CAD files can be purchased through Kochman Consultants, Ltd. at kclcad.com.