

Wall Mount Hand Sinks



viodei:						
Project.						

Item #:

Quantity: _

Model HS-11



Model HS-12



Model HS-14

Fabrication:

One piece 304 series stainless steel All seams tig welded and polished

Bowl:

Deep drawn with stamped rim to prevent spillage

Wall Mounting Bracket:

Offset design for added strength

Electronic Faucet:

Solid Brass Heavy Duty Faucet. Operates on 6V battery with a 1-3 year battery life based on usage. Built-in low battery indicator light. Infrared sensor in front turns water on and off. Sealed waterproof construction. 30 second time out and 2 second closing delay. 1 5/8" faucet hole cutout

Drain:

Stainless Steel

Drain with Overflow:

Stainless Steel with plastic overflow tube and inlet

Plumbing:

1/2" IPS hot and cold water 1 1/2" IPS drain outlet

Low Lead Compliance:

Low Lead Compliant faucet options are available to meet California AB-1953 and Vermont S152 standards

Model HS-13



Model HS-15

Model HS-22

Model HS-16





Model HS-30









Metal Corporation

100 Haul Road, Wayne, New Jersey 07470 www.krowne.com sales@krowne.com Approved By: __

Due to our commitment to continued product improvement, specifications are subject to change without notice

Phone: 800-631-0442 Fax: 973-872-1129



Wall Mount Hand Sinks



Model: Project: Item #: Quantity: HS-12 HS-13 HS-11 15 lbs. 30 lbs. 14 lbs. **Electronic Electronic Electronic Faucet Faucet Faucet** 1 5/8" electronic faucet hole cutout 1 5/8" electronic faucet hole cutout **HS-14 HS-15 HS-16** 36 lbs. 90 lbs 26 lbs. **Foot Pedal Knee Valve Knee Valve** Faucet **Faucet Faucet** Install Fauc Supply 3' HS-30 **HS-22** HS-26 14 lbs. 10" **DRAWING DRAWING COMING SOON COMING SOON** 18-1/2" 10 Options: check box(es) for required option(s) ☐ H-100 Chrome Plated 1 1/2" IPS P-Trap ☐ H-110 Side Support Brackets ☐ H-101 Deck Mount Soap Dispenser Soap & Towel Dispenser □ H-111 ☐ H-103 Wrist Handle Kit Upgrade - Low Lead Wrist Handle Faucet ☐ H-104 Wall Mount Soap Dispenser ☐ H-109 Upgrade - Royal Low Lead Faucet ☐ H-105 Wall Mount Towel Dispenser ☐ H-200 **Upgrade** - Commerical Low Lead Faucet ☐ H-106 One Side Splash



☐ H-107 Two Side Splashes

☐ H-108 Stainless Steel Skirt

Plumbing Requirements:

- Install 36" Working Height
- 1/2" Faucet Supply 12" from Floor
- 1 ¹/₂" Drain Line 23 ¹/₄" from Floor

Approved By:

Due to our commitment to continued product improvement, specifications are subject to change without notice

Metal Corporation

100 Haul Road, Wayne, New Jersey 07470 www.krowne.com sales@krowne.com

