

"The Inventor & World Leader in Food Processors"

COMPACT POWER MIXERS

CMP250V.V., CMP300V.V., CMP350V.V., CMP400V.V.

Compact Power Mixers

With 10", 12", 14" and 16" immersible Shafts



CMP400V.V. CMP350V.V. CMP300V.V. CMP250V.V.

Compact Power Mixers are ideal for liquefying soups, sauces, pureeing

Conforms to UL NSF Std 763 Std 8 Certified to CAN/CSA Std C22.2 No. 195 ETL LISTED 9900098

fruits and vegetables with a portable easy to handle unit.



All Robot Coupe Compact Power Mixers have ergonomically designed handles to reduce user fatigue, on-off control button with lock button, variable speed control button, splash guards, watertight seals, powerful motor, patented removable bell and knife assembly easily disassembled for unmatched sanitation.

- CMP250V.V. Variable Speed
 Compact Power Mixer with Mixer
 Attachment with 10" stainless steel
 immersible shaft. Processing Capacity
 – 16 quarts. Variable speed of 5,000
 to 10,000 RPM.
- CMP300V.V. Variable Speed
 Compact Power Mixer with Mixer
 Attachment with 12" stainless steel
 immersible shaft. Processing Capacity
 – 32 quarts. Variable speed of 5,000
 to 10,000 RPM.
- CMP350V.V. Variable Speed
 Compact Power Mixer with Mixer
 Attachment with 14" stainless steel
 immersible shaft. Processing Capacity
 – 50 quarts. Variable speed of 5,000
 to 10,000 RPM.
- CMP400V.V. Variable Speed
 Compact Power Mixer with Mixer
 Attachment with 16" stainless steel
 immersible shaft. Processing Capacity
 – 55 quarts. Variable speed of 5,000
 to 10,000 RPM.
- 1 year parts and labor warranty.

Robot Coupe U.S.A., Inc.

P.O. Box 16625 Jackson, MS 39236-6625 1-800-824-1646 • (601) 898-8411 FAX: (601) 898-9134

www.robotcoupeusa.com • e-mail: info@robotcoupeusa.com

SPECIFICATIONS ON REVERSE SIDE



COMPACT POWER MIXERS

CMP250V.V., CMP300V.V., CMP350V.V., CMP400V.V.

"The Inventor & World Leader in Food Processors"

Specifications

STANDARD MODEL: Variable Speed Compact Power Mixer with stainless steel mixer attachment with removable stainless steel knife and mixer blade, splash guard and disassembly tool. Immersible stainless steel shaft length:

CMP250V.V. - 10" CMP300V.V. - 12" CMP350V.V. - 14" CMP400V.V. - 16"

ELECTRICAL:

CMP250V.V. – 120V, 60Hz, single phase. **CMP300V.V.** – 120V, 60Hz, single phase. **CMP350V.V.** – 120V, 60Hz, single phase. **CMP350V.V.** – 120V, 60Hz, single phase.

Contact your local electrician for local code requirements.

MOTOR

CMP250V.V. – 3.0 Amps, 270 Watt, Single Phase; Variable Speed 5,000-10,000. **CMP300V.V.** – 3.2 Amps, 300 Watt, Single Phase; Variable Speed 5,000-10,000. **CMP350V.V.** – 3.5 Amps, 350 Watt, Single Phase; Variable Speed 5,000-10,000. **CMP350V.V.** – 3.5 Amps, 380 Watt, Single Phase; Variable Speed 5,000-10,000.

SWITCHING: On/off control button, variable speed control, lock button for continuous operation, safety button.

PROCESSING CAPACITY:


CMP250V.V. – Up to 16 quarts CMP300V.V. – Up to 32 quarts CMP350V.V. – Up to 50 quarts CMP400V.V. – Up to 55 quarts


WEIGHT:


CMP250V.V. - 11 lbs. CMP300V.V. - 11 lbs. CMP350V.V. - 11 lbs. CMP400V.V. - 12 lbs.


STANDARDS:

ETL electrical & sanitation, cETL (Canada)









Robot Coupe U.S.A., Inc.

P.O. Box 16625 Jackson, MS 39236-6625 1-800-824-1646 (601) 898-8411

FAX: (601) 898-9134 www.robotcoupeusa.com

e-mail: info@robotcoupeusa.com

Distributed by: