

BUNN®

AXIOM™ 12 Cup Automatic Coffee Brewer

ITEM#

PROJECT

DATE



Model AXIOM-15-3

(decanters sold separately)

Dimensions: 18.9" H x 8.5" W x 17.8" D
(48cm H x 21.6cm W x 45.2cm D)

Features

AXIOM Automatic Coffee Brewer

- Large 200 oz. (5.9 litres) tank provides back-to-back brewing capacity.
- Adjusts automatically to varying water pressure.
- For high lime areas, BrewLOGIC® technology calculates flow rate and adjusts brew time to maintain consistent pot levels.
- BrewWIZARD® technology simplifies brewer programming with a LCD display. Set brew level, cold brew lock-out and tank temperature from the front of the machine.
- Electronic diagnostics and built in tank drain make service easier.
- Ensures coffee brew quality with cold brew lock out capability.
- SplashGard® funnel deflects hot liquids away from the hand.
- Coffee extraction controlled with pre-infusion, pulse brew and digital temperature control.
- Automatic warmer shut-off.
- Energy-saver mode reduces tank temperature during idle periods.
- Hot water faucet.

For current specification sheets and other information, go to www.bunn.com.

Related Products

Easy Clear® EQ-17-TL

Product No. : 30200.1000



Easy Clear® ED-17-TL

Product No. : 30201.1001

Paper Filter Pack

Product No. : 20115.0000

Packed per case: 1,000



Easy Pour® black decanter

Product No. : 06100.0101

Quantity: 1 (also packaged in quantities of 2, 3, 6, 12, & 24)



Easy Pour® orange decanter (for decaf)

Product No. : 06101.0101

Quantity: 1 (also packaged in quantities of 2, 3, 6, 12, & 24)



1GPR SS Portable Server on an RWS1 Warmer

1GPR Product No. : 12487.0001*

RWS1 Product No. : 12203.0010

*Also available with side handles or black decor.



Model

AXIOM-15-3

AXIOM-35-3

Agency Listing



Patents Apply

10/09

A1.4a


Dimensions & Specifications

Model	Product #	Volts	Amps	Tank Heater Watts	Total Watts	Brewing Capacity	Cu. Ft.	Shipping Weight	Cord Attached
AXIOM-15-3 <i>1 lower/2 upper</i>	38700.0000	120	15	1425	1800	4.2 gal./hr.	4.0	30 lbs.	Yes
AXIOM-35-3 <i>1 lower/2 upper</i>	38700.0001	120/240	17.5	3500	3850	7.5 gal./hr.	4.0	30 lbs.	No
AXIOM-15-3 <i>3 lower warmers</i>	38700.0002	120	15	1425	1800	4.2 gal./hr.	4.0	31 lbs.	Yes
AXIOM-35-3 <i>3 lower warmers</i>	38700.0003	120/240	17.5	3500	3850	7.5 gal./hr.	4.0	31 lbs.	No

Brewing capacity: based upon incoming water temp of 60°F (140°F rise) per 1/2 gallon brew time of 4 minutes.
Models listed as 120/240V must be connected to 240V electrical service. Please refer to the installation manual.

Electrical: 120 volt, 15 amp models require 2-wires plus ground service rated 120V, single phase, 60 Hz.
120/240 volt models require 3-wires plus ground service rated 120/240V, single phase, 60 Hz.
An internal terminal block is configured for connection to a 3-wire plus ground.

Plumbing: 20-90 psi (138-621 kPa). Machines supplied with 1/4" male flare fitting.



Bunn-O-Matic® Corporation - 1400 Stevenson Drive Springfield, Illinois 62703 • 800-637-8606 • 217-529-6601 • Fax 217-529-6644 • www.bunn.com

BUNN® practices continuous product research and improvement. We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.

All dimensions shown in inches.

Tundra Specialties

10/09 © Bunn-O-Matic Corporation