

FE SERIES - FABRICATED SINKS



Approx.

One & Two Compartments

Bowl

Drbd. Length



Rolled Rim Edge For Additional Strength

Width

Bowl Size

Length

ltem #:	Qty #:	
Model #:		
Project #:		

Drbrd.



K-700Removable Side Splashes Fits Left OR Right Side

	WODEL#	L	W	A & B	Depth	Size	Drbrds.	Location	WL.	Cubes
1 COMP.	FE-1-1515-X	20"	20 3/4"	15"x15"	12"	N/A	0	None	38 lbs.	11
	FE-1-1514-15RLX	45"	20 3/4"		14"	N/A	2	R&L	65 lbs.	22
	FE-1-1620-X	21"	25 3/4"	16"x20"	12"	N/A	0	None	42 lbs.	12
	FE-1-1620-18RorL-X	36 1/2"	25 3/4"		12"	18"	1	R or L	55 lbs.	18
	FE-1-1620-18RL-X	52"	25 3/4"		12"	18"	2	R&L	67 lbs.	25
	FE-1-1812-X	23"	23 3/4"	18"x18"	12"	N/A	0	None	42 lbs.	13
	FE1-1812-18RorL-X	38 1/2"	23 3/4"		12"	18"	1	R or L	57 lbs.	22
	FE1-1812-18RLX	54"	23 3/4"		12"	18"	2	R&L	65 lbs.	23
	FE-1-1824-X	23"	29 3/4"		14"	N/A	0	None	60 lbs.	16
	FE-1-1824-24RorL-X	44 1/2"	29 3/4"	18"x24"	14"	24"	1	R or L	105 lbs.	28
	FE-1-1824-24RL-X	66"	29 3/4"		14"	24"	2	R&L	110 lbs.	26
	FE-1-2424-X	29"	29 3/4"		14"	N/A	0	None	90 lbs.	20
	FE-1-2424-24RorL-X	50 1/2"	29 3/4"	24"x24"	14"	24"	1	R or L	103 lbs.	34
	FE-1-2424-24RLX	72"	29 3/4"		14"	24"	2	R&L	122 lbs.	44
2 COMP.	FE-2-1620-X	37"	25 3/4"	16"x20"	12"	N/A	0	None	72 lbs.	18
	FE-2-1620-18RorL-X	52 1/2"	25 3/4"		12"	18"	1	R or L	84 lbs.	25
	FE-2-1620-18RL-X	68"	25 3/4"		12"	18"	2	R&L	100 lbs.	32
	FE-2-1812-X	41"	23 3/4"	18"x18"	12"	N/A	0	None	65 lbs.	18
	FE-2-1812-18RorL-X	56 1/2"	23 3/4"		12"	18"	1	R or L	78 lbs.	26
	FE-2-1812-18RLX	72"	23 3/4"		12"	18"	2	R&L	84 lbs.	44
	FE-2-2424-X	53"	29 3/4"	24"x24"	14"	N/A	0	None	124 lbs.	33
	FE-2-2424-24RorL-X	74 1/2"	29 3/4"		14"	24"	1	R or L	132 lbs.	38
	FE-2-2424-24RLX	96"	29 3/4"		14"	24"	2	R&L	140 lbs.	50

FEATURES:

Backsplash has tile edge for ease of installation.

Sink bowls are 3/4" coved corner and meet NSF requirements.

Rolled Rim Edge for additional strength.

15"x15", 16"x20" & 18"x18" Sink Bowls are 12" deep.

18"x24" & 24"x24" Sink Bowls are 14" deep.

9" Backsplash.

CONSTRUCTION:

All TIG welded.

Welded areas blended to match adjacent surfaces and to a satin finish.

Gussets welded to a die-embossed reinforced plate.

MATERIAL:

1 5/8" diameter galvanized legs with

1" adjustable plastic bullet feet.

Entire unit is 18 gauge 304 stainless steel.

Gussets - galvanized steel.

MECHANICAL:

- Supply is 1/2" IPS hot & cold.
- Faucet holes on 8" centers.
- Faucets are not included (see accessories).
- Waste drains are 1 1/2" IPS S/S basket type, located in center of sink bowl, and are included.

OPTIONAL:

- FE-SS-12 S/S Leg Upgrade For Sinks w/ 12" Deep Bowls
- FE-SS-14 S/S Leg Upgrade For Sinks w/ 14" Deep Bowls



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 8:00 pm E.S.T.

For Orders & Customer Service:

Email: customer@advancetabco.com or Fax: 631-242-6900

For Smart Fabrication™ Quotes:

Email: smartfab@advancetabco.com or Fax: 631-586-2933

DIMENSIONS and SPECIFICATIONS

TOL Overall: ± .500" Interior: ± .250"

ALL DIMENSIONS ARE TYPICAL







