




ConturaSeries®
RECESSED PAPER TOWEL
DISPENSER AND WASTE
RECEPTACLE

B-43944



Rough Wall Opening
16" (405mm) wide
54-3/4" (1390mm) high
4" (100mm) minimum
recessed depth

MATERIALS:

To retrofit TowelMate into existing installed units manufactured prior to April 2010, order TowelMate Accessory Bobrick Part No. 3944-130

continued...

Waste Receptacle — 18-8 S, type-304, 18-gauge (1.2mm) stainless steel with satin-finish. Formed, one-piece, seamless construction. Removable front panel has same degree of arc as front of paper towel dispenser door and other Bobrick ConturaSeries washroom accessories. Top edge hemmed for safe handling. Radius on side edges of waste receptacle match corners and edges of door and other ConturaSeries accessories. Secured to cabinet with two keyholes over studs on bottom and two tamper-resistant setscrews on top. Capacity: 15.0-gal. (56.8-L).

LinerMate™ Trash Liner Holder — Molded plastic trash liner holder sleeve and U-shaped 18-8 S, type-304, 20-gauge (0.91mm) stainless steel support strap; riveted construction. Molded plastic trash liner holder has arc at front and same shape as inside of waste receptacle area. Removable for servicing.

To retrofit LinerMate into existing installed units manufactured prior to December 2009, order LinerMate Accessory Bobrick Part No. 43944-134

OPERATION:

Paper towel dispenser will dispense C-fold or multifold paper towels without adjustment or use of adapters. Cable door-swing limiter prevents damage to washroom accessories and walls. Load paper towels in towel tray, and then pull one sheet of paper towel over the TowelMate towel rod and out to conceal rod and start dispense. Front of waste receptacle panel is removable for cleaning cabinet interior. To insert disposable trash liner, lift LinerMate trash liner holder up and forward and rest over edge of waste receptacle front panel with the bottom notches of LinerMate engaged on top front edge of receptacle. Place disposable trash line inside LinerMate and fold disposable trash line over molded sleeve. Tie a knot in the corner of the disposable trash line, then place LinerMate with disposable trash line back into receptacle. To empty, gather disposable trash line from LinerMate liner holder sleeve and lift disposable trash line up. Additional LinerMate may be added using Bobrick Part No. 43944-134.

INSTALLATION:

Provide framed rough wall opening 16" wide x 54-3/4" high (405 x 1390mm). Minimum recessed depth required to finish face of wall is 4" (100mm). Allow clearance for construction features that may protrude into rough wall opening from opposite wall. Coordinate with mechanical engineer to avoid pipes, vents, and conduits. If unit projects above top of wainscot, provide aluminum channel or other filler to eliminate gap between flange and finish face of wall. Mount unit in wall opening with shims between framing and cabinet at all points indicated by an S, then secure unit with #8 x 1-1/4" (4.2 x 32mm) screws (not furnished).

SPECIFICATION:

Recessed paper towel dispenser and waste receptacle shall be type-304 stainless steel with all-welded construction; exposed surfaces shall have satin-finish. Front of paper towel dispenser door and waste receptacle shall have same degree of arc and match other Bobrick ConturaSeries accessories in the washroom. Radius on corners and edges of flange, door, and waste receptacle shall complement other Bobrick ConturaSeries washroom accessories. Flange shall be drawn, one-piece, seamless construction. Paper towel dispenser door shall be drawn, 18-gauge (1.2mm), one-piece, seamless construction; secured to cabinet with a full-length stainless steel piano-hinge; and equipped with a stainless steel cable door-swing limiter and flush tumbler lock keyed like other Bobrick washroom accessories. Paper towel dispenser shall dispense 600 C-fold or 800 multifold paper towels. Unit equipped with TowelMate consisting of a 90° return towel guide angle inside cabinet to prevent paper towels from falling forward out when door is opened for servicing and a Nylon Rod across the center of the towel tray to dispense paper towels one at a time without bulging, sagging, bunching or falling thru the opening. Waste receptacle shall have a formed, 18-gauge (1.2mm), one-piece, seamless, removable front panel with top edge hemmed. LinerMate trash liner holder shall have a molded plastic trash liner holder sleeve with a 20-gauge (0.91mm), U-shaped support strap; riveted construction. Liner holder shall have an arc at front and same shape as inside of waste receptacle area. LinerMate facilitates installation and removal of disposable trash liners without liner overhang on front panel of waste receptacle. Capacity of waste receptacle shall be 15.0-gal. (56.8-L).

Recessed Paper Towel Dispenser And Waste Receptacle shall be Model B-43944 of Bobrick Washroom Equipment, Inc., Clifton Park, New York; Jackson, Tennessee; Los Angeles, California; Bobrick Washroom Equipment Company, Scarborough, Ontario; Bobrick Washroom Equipment Pty. Ltd., Australia; and Bobrick Washroom Equipment Limited, United Kingdom.