

Project _____

Item # _____

Quantity _____



GLOBE FOOD EQUIPMENT COMPANY

Compact Manual Slicers

C9 / C10 / C12



C12



C9 / C10 / C12 Compact Manual Slicers

Globe Chefmate™ Models

- ☐ C9 - 9" Diameter Knife Manual Slicer
- ☐ C10 - 10" Diameter Knife Manual Slicer
- ☐ C12 - 12" Diameter Knife Manual Slicer

Standard Features

- Hard chromed, special alloy hollow ground knife
- Powerful knife motors ¼ HP (C9, C10), ½ HP (C12)
- Motor overload protection with manual reset
- Top mounted all metal knife sharpener
- 0 to 9/16" slice thickness
- Anodized aluminum construction with seamless edges and radius corners
- Oversized positive traction grooved belt drive
- Gravity feed food chute
- Lightweight and compact space saving design
- Dual purpose handle with improved ergonomic design
- Removable, easy-to-clean chute, slice deflector, knife cover and sharpener
- Bottom enclosure
- Attached 5 foot, 4 inch cord and plug



Standard Warranty

- One-year parts and labor

Approved By: _____

Date: _____



GLOBE FOOD EQUIPMENT COMPANY
www.globeslicers.com

2153 Dryden Rd.
 Dayton, OH 45439
 Phone: 937-299-5493
 Phone: 800-347-5423
 Fax: 937-299-4147



Compact Manual Slicers

C9 / C10 / C12

Specifications

Finish: Heavy gauge anodized aluminum that is stain resistant, long lasting and easy to clean.

Motor: Powerful motors, fan cooled, permanently lubricated ball bearings ensure quiet operation. Thermal overload protection included.

C9: ¼ HP, 115-60-1, 2 amps
C10: ¼ HP, 115-60-1, 2.5 amps
C12: ½ HP, 115-60-1, 3 amps

Manual Reset Button: Motor overload protection allows the operator to reset the slicer manually.

Knife Drive: Knife is driven by a positive grooved belt that works well in light duty applications.

Slice Thickness: Food can be sliced from 0 to 9/16" thick.

Top Mounted Sharpener: Sharpener is all metal construction and is top mounted for easy access. A two stone, dual action design allows you to quickly return a razor sharp edge to your knife. Sharpener is removable for cleaning.

Hollow Ground Knife: Hard chromed, special alloy hollow ground blade lasts longer and sharpens easily.

C9: Nominal 9" diameter
C10: Nominal 10" diameter
C12: Nominal 12" diameter

On/Off Controls: Moisture protected separate on/off push button type.

Ball Bearing Chute Slide System: Ball bearing system ensures smooth and easy movement of the food chute assembly.

Knife Hub: Knife hub bearings, belt, and motor are fully enclosed, protecting them from moisture.

Knife Cover: The knife cover is designed to fit on the slicer only one way to ensure accurate placement every time.

Table Rod: Separate table support rod is protected by the table casting and cover.

Bottom Enclosure: Components are safeguarded by a cover protecting them from food and other debris.

Slice Deflector: Deflector is securely fastened to the slicer; simple to remove without tools and easy to clean.

Rubber Feet: Supplied with nonslip rubber feet.

Capacity:

C9: 6.5" H, 7.25" W, 6.25" Dia.
(16.5cm, 18.4cm, 15.9cm)

C10: 7.25" H, 8.62" W, 6.87" Dia.
(18.4cm, 21.9cm, 17.4cm)

C12: 8.62" H, 9.75" W, 8" Dia.
(21.9cm, 24.8cm, 20.3cm)

Cord & Plug: Attached 5 foot, 4 inch flexible 3-wire cord and plug fits a grounded receptacle.

Dimensions (C9):

Overall Length = 18" (45.7cm)
Overall Width = 17" (43.2cm)
Overall Height = 15" (38.1cm)
Freight Class: 77.5
Net Weight: 31.7 lbs. (14.4kg.)
Shipping Weight: 40 lbs. (18.1kg.)
Box Dimensions:
19"W x 16.75"D x 14.75"H
(48cm W x 42cm D x 38cm H)

Dimensions (C10):

Overall Length = 19.5" (49.5cm)
Overall Width = 17" (43.2cm)
Overall Height = 15" (38.1cm)
Freight Class: 77.5
Net Weight: 32 lbs. (14.5kg.)
Shipping Weight: 42 lbs. (19.1kg.)
Box Dimensions:
22"W x 17.75"D x 15.75"H
(55cm W x 45cm D x 40cm H)

Dimensions (C12):

Overall Length = 22.5" (57.2cm)
Overall Width = 20" (50.8cm)
Overall Height = 17.5" (43.2cm)
Freight Class: 77.5
Net Weight: 49 lbs. (22.3kg.)
Shipping Weight: 59 lbs. (26.8kg.)
Box Dimensions:
25.75"W x 21.5"D x 19.75"H
(65cm W x 55cm D x 50cm H)



GLOBE FOOD EQUIPMENT COMPANY

www.globeslicers.com

2153 Dryden Rd.
Dayton, OH 45439
Phone: 937-299-5493
Phone: 800-347-5423
Fax: 937-299-4147

Printed in U.S.A. 4-2009

Specifications are subject to change without notice.