



Item # _____

Job _____


SmartWall G3™ System

Organized, efficient wall space at work.


A unique storage and work station system for often underutilized space – empty walls. SmartWall G3 and its system of integrated wall tracks offer the flexibility to add wall shelving and wall mounted task stations where needed throughout a facility. The use of the system around and above sinks, work tables, and equipment will keep these areas cleaner and more organized. SmartWall G3 can become an integral part of everyday operating processes to improve efficiencies and ultimately the return on investment (ROI).



Task Station (medium duty) with accessories for a sink /prep area.



Task Station (standard duty) with accessories for a food prep area.



Adjustable Wall Shelving

- **Flexible, Robust Design:** Wall tracks and uprights are designed to interface with wood studs, plywood, concrete, and other suitable wall structures.
- **Configurations**
 - Task Stations:** unique combinations of wall tracks, shelves, grids, and accessories.
 - Adjustable Wall Shelving:** standard Metro Super Erecta wire and solid, MetroMax Q, and MetroMax i™ shelves can be used with the SmartWall G3 shelf supports.
- **Easy to Adjust:** Uprights and grid brackets can be easily repositioned along the track.
 - Heavy gauge uprights:** 1-1/2" (38mm) vertical adjustment of shelves and grids
 - Grids:** 3" (76mm) vertical and horizontal adjustment of accessories
- **Easy to Install:** Simply attach the wall tracks to a proper mounting structure. The wall tracks provide a level mounting surface for uprights and grid brackets. Hang the uprights or grid brackets from the track. Configure the task station or wall shelving. Finally, secure the uprights or bottom grid brackets to the wall.
- **Easy to Clean:** Shelves, shelf supports, and grids can easily be removed for thorough cleaning of walls. Wall tracks and uprights can easily be wiped clean.
- **Durable Finishes:** Super Erecta Brite for dry environments; Metroseal 3 epoxy for wet or damp environments with built-in Microban® antimicrobial product protection to inhibit the growth of bacteria, mold, mildew, and fungus that cause odors and product degradation.

*MICROBAN and the MICROBAN symbol are registered trademarks of the Microban Products Company, Huntersville, NC.



InterMetro Industries Corporation
North Washington Street
Wilkes-Barre, PA 18705
www.metro.com



SmartWall G3™ System


10.42

Specifications

- **Wall tracks:** 12 gauge cold rolled steel; obround mounting holes located at 8" (204mm) increments; first and last holes are located 4" (102mm) from the ends of the track; obround hole dimensions (1/8 x 3/4"; 3 x 19mm). Wall tracks include stop fasteners for the ends of the tracks and joiner plates for connecting adjacent tracks.
- **Uprights:** 12 gauge cold rolled steel; slotted every 1-1/2" (38mm); 1-1/8" (29mm) diameter mounting holes are spaced every 6" (152mm) along the upright
- **Shelf Supports:** cold rolled steel; sleeve is high density polyethylene (HDPE)
- **Shelves:** standard Super Erecta wire and solid, MetroMax Q, or MetroMax i™ shelves may be used. See catalog sheets 10.01, 10.20, 9.20, and 9.21 for shelving specifications.
- **Finishes:** standard finishes for components are Metro BRITE for dry environments and Metroseal 3 epoxy for wet or damp environments. Metroseal 3 contains built-in Microban® antimicrobial product protection to protect the product from bacteria, mold, mildew, and fungus that cause odors and product degradation.
- **Wire Grids:** 1/4" (6mm) diameter cold rolled steel wire
- **Grid bracket kits:** 14 gauge, type 304 stainless steel
- **Grid Accessories:** see catalog sheet 10.44
- **Cleaning instructions:** Clean with mild detergents and damp cloths. Do not use abrasive materials because these may damage the protective coatings.

Configurations

SmartWall G3 offers limitless configurations. The following are examples and meant to demonstrate how to configure the basic product. Accessories can be added to these base units.




Task Station (medium duty) Components [qty]

- [1] Wall Track
- [2] Uprights
- [4] Single shelf supports
- [2] Super Erecta shelves
- [1] Grid (same length as shelf)




Adjustable Wall Shelving Components [qty]

- [2] Wall Tracks
- [3] Uprights
- [4] Single shelf supports
- [2] Double (intermediate) shelf supports
- [4] Super Erecta shelves



Task Station (standard duty) Components [qty]

- [1] Wall Track
- [1] Grid bracket kit (cat. no. SWGB1)
- [1] Grid
- [1] Grid shelf with retaining edge
[same length as grid]



Task Station (standard duty) Components [qty]

- [1] Grid bracket kit (cat. no. SWGB2)
- [1] Grid



SmartWall G3

Components

Wall Tracks (minimum one per system)

- Joiner plates and stop fastener hardware included. Does not include hardware to mount wall tracks to the wall.
- Packed one track per carton.
- Replacement joiner plate (1) and stop fastener hardware (2 sets): cat. no. RPTRK-HDWE



Cat. No.	Cat. No.	Actual Length		Actual Depth		Actual Width		Approx. Pkd. Wt.	
Brite zinc	Metroseal 3	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(lbs.)	(kg)
SW40BR	SW40K3	40	1016	3/4	19	1-9/16	40	5.0	2.2
SW56BR	SW56K3	56	1423	3/4	19	1-9/16	40	6.0	2.6
SW72BR	SW72K3	72	1829	3/4	19	1-9/16	40	7.0	3.1


NOTE: Tracks can be cut to length, but Metro does not provide this service. Touch up paint for Metroseal 3 tracks is available. Cat. No. TP-K2

Medium duty configurations consist of wall tracks, uprights, shelf supports, and grids

Uprights (for medium duty applications, minimum two per system)


- Built-in slots allow shelf supports and grids to attach without tools or hardware.
- 1-1/2" (38mm) slot spacing allows shelves and grids to be adjusted on 1-1/2" (38mm) increments
- Sold by the piece; packed two per carton

Cat. No.	Cat. No.	Number of slots	Actual Length		Actual Width		Actual Depth		Approx. Pkd. Wt.	
Brite zinc	Metroseal 3		(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(lbs.)	(kg)
SWU15BR	SWU15K3	7	16	406	1-1/8	29	1-7/8	48	1.8	0.8
SWU30BR	SWU30K3	17	31	787	1-1/8	29	1-7/8	48	3.5	1.5
SWU45BR	SWU45K3	26	44-1/2	1130	1-1/8	29	1-7/8	48	5.3	2.3




Shelf Supports

- Mount directly to slotted uprights
- Single shelf supports are used on each end of a stand-alone unit or side-by-side unit (pictured). Sold by the piece; packed two per carton.
- Double (intermediate) shelf supports are used when configuring side-by-side wall shelving units. Sold by the piece; packed one per carton.



Single Shelf Supports

Cat. No.	Cat. No.	Fits shelf depth	Actual Length		Actual Width		Actual Height		Approx. Pkd. Wt.	
Brite zinc	Metroseal 3		(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(lbs.)	(kg)
SWS14BR	SWS14K3	14" (355mm)	16-9/16	421	1-1/2	38	8-3/16	208	2.5	1.1
SWS18BR	SWS18K3	18" (457mm)	20-9/16	522	1-1/2	38	8-3/16	208	3.0	1.3
SWS21BR	SWS21K3	21" (530mm)	23-9/16	598	1-1/2	38	8-3/16	208	3.5	1.5
SWS24BR	SWS24K3	24" (610mm)	26-9/16	675	1-1/2	38	8-3/16	208	3.5	1.5



Double (Intermediate) Shelf Supports

Cat. No.	Cat. No.	Fits shelf depth	Actual Length		Actual Width		Actual Height		Approx. Pkd. Wt.	
Brite zinc	Metroseal 3		(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(lbs.)	(kg)
SWD14BR	SWD14K3	14" (355mm)	16-9/16	421	1-1/2	38	8-3/16	208	2.5	1.1
SWD18BR	SWD18K3	18" (457mm)	20-9/16	522	1-1/2	38	8-3/16	208	3.0	1.3
SWD21BR	SWD21K3	21" (530mm)	23-9/16	598	1-1/2	38	8-3/16	208	3.5	1.5
SWD24BR	SWD24K3	24" (610mm)	26-9/16	675	1-1/2	38	8-3/16	208	3.5	1.5

NOTE: replacement plastic sleeve for shelf support; cat. no. RP-SPSLV

Product Notes:

- SmartWall G3 tracks, uprights, and shelf supports are not compatible with earlier generations of original SmartWall or SmartWall Plus.
- When configuring task stations with uprights, choose shelves and grids of the same length. Longer grids may be used but must not overhang the upright by more than 6" (152mm) on either side.
- Grids can be mounted directly behind shelves, but shelf supports and grids cannot occupy the same slots on the upright. Once the grid has been mounted to the upright, the shelf support can be mounted to its own slots and can be adjusted on 3" (76mm) increments within the grid space.





Reference: Note C.


Standard duty configurations consist of wall tracks (optional), grid brackets, and grids.
Grid Mounting Brackets (for standard duty applications without uprights)

- For standard duty applications, grids may be mounted directly to the track or directly to the wall without a track using SmartWall G3 grid bracket kits.

Cat. No.	Description	Approx. (lbs.)	Pkd. Wt. (kg)
SWG B1	Bracket kit to connect grid to wall track; Consists of (2) top brackets and (4) bottom brackets	2.0	0.9
SWG B2	Direct wall mount bracket kit; Consists of (6) bottom brackets	2.0	0.9


 Bottom bracket:
connects to wall

 Top bracket:
connects to track

Grids

- Grids are a mounting surface for task management accessories.
- See spec sheet 10.43 for grid accessories.

Cat. No.	Cat. No.	Width x Length		Approx. Pkd. Wt.	
Plated	Metroseal 3	(in.)	(mm)	(lbs.)	(kg)
-	WG1830K3	18x30	457x760	7.5	3.3
-	WG1836BR WG1836K3	18x36	457x914	9.0	4.1
-	WG1848BR WG1848K3	18x48	457x1219	12.0	5.4
-	WG1860BR WG1860K3	18x60	457x1524	14.0	6.4
-	WG2436K3	24x36	610x914	12.0	5.4
-	WG2448K3	24x48	610x1219	15.5	7.0
-	WG3036K3	30x36	760x914	12.8	5.8
-	WG3048K3	30x48	760x1219	16.5	7.5
PBA-GPC	-	33x54	838x1370	21.0	9.5

NOTE:

- Grids can mount directly to the uprights without brackets.
- Mount a grid directly to the track with bracket kit model SWGB1.
- Mount a grid directly to the wall without a track with bracket kit model SWGB2.

Weight capacities are based on a **stand-alone unit with a wall track, two uprights, and any combination of shelves and grids.**

Structures into which wall tracks are mounted	Per Unit
Wood Studs	400 lbs. (180kg)
Woods Studs with cross-stud reinforcement	400 lbs. (180kg)
Plywood: Minimum thickness - 1/2" (13mm)	400 lbs. (180kg)
Concrete	200 lbs. (90kg)
Metal Studs	100 lbs. (45kg)
Environmental room and walk-in cooler walls (appropriately reinforced)	consult your Metro representative
Weight capacity per shelf (Super Erecta, MetroMax Q, MetroMax i)	250 lbs. (113kg) not to exceed the overall stated weight capacity of the unit based on the wall structure

Weight capacities for adjacent units that share an upright.

General Rule	Unit: 1/2 the stated weight capacity of a stand-alone unit based on the wall structure Shelf: 125 lbs. (56kg) not to exceed the overall weight capacity of the unit based on the wall structure.
--------------	---

Weight capacities for grids and grid shelves

Grid	250 lbs. (113kg)
Grid shelf with retaining edge	50 lbs. (22.5kg)



Stand-alone unit



Adjacent units with a shared upright



Grid and Grid shelf


InterMetro Industries Corporation

North Washington St.
Wilkes-Barre, PA 18705

For Product Information:
U.S. and Canada: 1.800.433.2232
Latin America: 1.561.333.3824
Europe: +31(0)76.587.75.50
Asia/Pacific: +65.6567.8003
Middle East/Africa: +971.4.811.8286

L02-181

8/09

Information and specifications are subject to change without notice. Please confirm at the time of order.

